AXCS EQUIPMENT

HY-BRID LIFTS
ENGINEERED & BUILT IN USA

PS-1030 MICRO
PS-1430 MICRO
PS-1930 MICRO
SCISSOR

PRO SERIES
SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- Electric drive & steer
- Proportional controls
- LeakGuard®
- 110V-AC power to platform
- Indoor/outdoor operation settings
- Maintenance charger
- Intelligent control system
- No folding rails
- Dual maintenance locks
- Active tilt alarm
- Active load-sensing
- Flashing beacon
- Horn
- All motion alarm
- Low floor load pressures
- Pothole protection
- Forklift pockets
- 8in inside turn radius
- EZ-Glide slide out extension
- 30% gradeability
- Solid rubber, non-marking wheels
- Default upper control setting
- Manual descent pull cable
- 2-year parts & labor warranty
- 5-year structural warranty

STANDARDS COMPLIANCE

- ANSI A92.20
- CSA B354.6:17
- EN 280-1:2022

OPTIONS

- Pipe rack
- Confined access
- AGM batteries
- Perimeter lights
- Telematics

PRO SERIES

SPECIFICATIONS		PS-1030	PS-1430	PS-1930
A	Working Height (1 Person Indoor)	**16 ft** 4.9 m	**20 ft** 6.1 m	**24.4 ft** 7.4 m
	Working Height (2 Person Indoor / 1 Person Outdoor)	**16 ft** 4.9 m	**16 ft** 4.9 m	**18 ft** 5.5 m
B	Platform Height Maximum (1 Person Indoor)	**10 ft** 3 m	**14 ft** 4.3 m	**18.4 ft** 5.6 m
	Platform Height Maximum (2 Person Indoor / 1 Person Outdoor)	**10 ft** 3 m	**10 ft** 3 m	**12 ft** 3.7 m
C	Platform Height Minimum	**25 in** 63.5 cm	**28 in** 71.1 cm	**31 in** 78.7 cm
D	Ground Clearance Elevated	**0.3 in** 0.8 cm	**0.3 in** 0.8 cm	**0.3 in** 0.8 cm
E	Ground Clearance Lowered	**3 in** 7.6 cm	**3 in** 7.6 cm	**3 in** 7.6 cm
F	Overall Length w/ Step	**69.5 in** 176.5 cm	**69.5 in** 176.5 cm	**69.5 in** 176.5 cm
G	Width	**30 in** 76.2 cm	**30 in** 76.2 cm	**30 in** 76.2 cm
H	Stowed Height	**68.3 in** 173.5 cm	**71.3 in** 181.1 cm	**74.3 in** 188.7 cm
I	Platform Length	**57.8 in** 146.8 cm	**57.8 in** 146.8 cm	**57.8 in** 146.8 cm
J	Platform Width	**21.8 in** 55.4 cm	**21.8 in** 55.4 cm	**21.8 in** 55.4 cm
	Slide Out Extension Deck Length	**30 in** 76.2 cm	**30 in** 76.2 cm	**30 in** 76.2 cm
	Wheelbase	**51 in** 129.5 cm	**51 in** 129.5 cm	**51 in** 129.5 cm
	Tires (Front/Rear)	**12 / 12 in** 30.5 / 30.5 cm	**12 / 12 in** 30.5 / 30.5 cm	**12 / 12 in** 30.5 / 30.5 cm
PERFORMANCE				
Rated Occupancy (Indoor/Outdoor)		**2 / 1 Person(s)**	**2 / 1 Person(s)**	**2 / 1 Person(s)**
Platform Capacity		**800 lbs** 362.9 kg	**700 lbs** 317.5 kg	**650 lbs** 294.8 kg
Slide Out Extension Deck Capacity		**250 lbs** 113.4 kg	**250 lbs** 113.4 kg	**250 lbs** 113.4 kg
Gradeability		**30%**	**30%**	**30%**
Inside Turn Radius		**8 in** 20.3 cm	**8 in** 20.3 cm	**8 in** 20.3 cm
Drive Speed Elevated		**0.7 mph** 1.1 km/h	**0.7 mph** 1.1 km/h	**0.6 mph** 1.0 km/h
Drive Speed Lowered		**2.4 mph** 3.9 km/h	**2.4 mph** 3.9 km/h	**2.4 mph** 3.9 km/h
Lift Speed (Up/Down)		**28 / 28 s**	**28 / 28 s**	**28 / 28 s**
Weight		**1500 lbs** 680.4 kg	**1780 lbs** 807.4 kg	**1985 lbs** 900.4 kg
Wheel Load at Minimum Capacity		**82.2 psi** 566.8 kPa	**97.5 psi** 672.2 kPa	**107 psi** 737.7 kPa
Wheel Load at 500 lbs Capacity		**100.8 psi** 695 kPa	**114.1 psi** 786.7 kPa	**122.2 psi** 842.5 kPa
Wheel Load at Maximum Capacity		**112 psi** 772.2 kPa	**120.7 psi** 832.2 kPa	**126.7 psi** 873.6 kPa
POWER				
Hydraulic Tank Capacity		**1.3 gal** 4.62 L	**1.3 gal** 4.62 L	**1.3 gal** 4.62 L
Battery		**2 x 12V Group 27**	**2 x 12V Group 27**	**2 x 12V Group 27**

This brochure is for illustrative purposes only and based on the latest information available at the time of printing.
AXCS Equipment reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment.
©2026 AXCS Equipment all rights reserved.
6|26 Part No. PS-00005